ECONO-LUX

AccentAwnings.com



Econo-Lux Retractable Awning

by **Accent Awning Company™**



Available Electronic Controls

- Plug-In Wind Sensor
- Plug-in Sun/Wind Sensor Remote Control

Optional Hood – Adds to the aesthetic appeal of your awning and provides additional fabric protection when in the retracted position

For your home or office, the *Econo-Lux* Awning system lowers incoming radiant heat by as much as 23%. Don't let today's high energy costs spoil your outdoor enjoyment. With its technological improvements and energy-saving design, the *Econo-Lux* by Accent Awnings® pays for itself in just a few short years.

Injoy years of trouble-free service with the **Econo-Lux** Awning System at a price designed to please even the most cost conscious consumer.







The Difference Is In Our Expertise

AccentAwnings.com





Now it's easy to control the sun with the *Econo-Lux* retractable awning. Operate by hand crank, interior switch or hand-held remote. The Somfy® motor's design meets or exceeds UL and CSA standards. This ensures years of quiet, trouble-free operation. All Somfy® motors & electronics are backed by a 5-year limited warranty and require no maintenance. Be sure to ask us about the wide array of options available such as automated sensors & remote control systems.

Fabric Colors Available



Features & Specifications

Fabric:

- Solution dyed acrylic Five (5) popular solid colors (Bone, Hunter Green, Costal Blue, Midnight Black & Burgundy)
- Marine/Awning grade
- Water Repellant Fade & Stain Resistant

Thread

- PTFE TEFLON thread manufactured by Coats®
- THREE TIMES more durable than bonded polyester

Hardware Finish:

 Electro-statically applied powder coated finish. Oven baked for superior durability

Hardware Colors:

• White (RAL 9010)

Arm Construction:

- Two-part spring loaded folding arm
- The arm consists of a thick-walled tubular aluminum extrusion with a cable connected to dual inner springs
- Arm joints are high quality cast aluminum, tumblepolished, then powder coated
- Cables and springs are teflon coated

Arm Projections:

• 5ft ~ 6.5ft ~ 8ft

Pitch Adjustment:

• Slope adjustment ranging from 5-85 degrees

Widths

• Three specific widths. 8'1" W ~ 12'0" W ~ 15'11" W

Mounting Bar:

40mm x 40mm powder coated 6063-T5 aluminum extrusion

Front Bar:

Custom extruded 6063-T5 aluminium powder coated profile

Roller Tube:

70mm and 78mm diameter galvanized steel

Operation:

- Manually Worm gear and crank handle
- Motorized Somfy® tubular motors housed inside the fabric roller tube

Nuts & Bolts:

- Aircraft quality stainless steel nuts and bolts utilized throughout construction and installation
- · Impervious to rust

Santa Ana